



WALL CONTROLS




**Model DH100W
Dehumidistat**

- Fits single-gang box
- Variable setting from 20% to 80 % relative humidity
- Dual voltage (24 V/120 V)




**Model P68WN (White)
Two-Funtion Control**

- Two independent 120 V, 15 Amp rocker switches (20 Amp total)
- Fits single-gang box
- For use with all Broan or NuTone fans and heaters within Amp rating




**Model P57WN (White)
Electronic Variable Speed Control (3 Amp)**

- Positive on/off action-dial for variable selection of air speeds and sound level
- 120 VAC, 3.0 Amp capacity
- Fits single-gang box
- Built-in radio noise suppressor
- Can be used with Broan Models 502, 503, 504, 505, 508, 509, 512, EC50, EC70, DX90, DX110, or NuTone 695C, 696NC, 671SP, 672SP




**Model P77DWN (White)
Four-Funtion Control**

- Specially designed for use with Sensaire® and Designer Series fan/lights
- Single switch provides three settings for fan sensor (on/auto/off) on sensing models. Remaining switches for light and night-light
- 120 VCA, Amp each rocker = 15, 15, 5 (20 Amp total)
- Fits single-gang box
- Includes switch function labels




**Model P59WN (White)
60-Minute Time Control**

- Operates continuously or for any set period up to 60 minutes
- Fits single-gang box
- 120 VAC, 20 Amp or 240 VAC, 10 Amp capacity
- Also recommended for low voltage (30 V Max.) applications
- For use with all Broan or NuTone fans and heaters within Amp rating




**Model P269WLN (White)
Two-Funtion Control with Indicator**

- Red light indicates power is on
- Specially designed for use with Ultra Silent™ fans and an auxiliary light source.
- Fits two-gang box
- 120 VAC, 20 Amp lighted switch; 120/240/277 VAC, 15 Amp unlighted switch




**Model P61WN (White)
15-Minute Time Control**

- Operates for any set period up to 15-minutes (no "continuous on" position)
- Fits single-gang box
- 120 VAC, 20 Amp or 240 VAC, 10 Amp capacity
- For use with all Broan or NuTone fans and heaters within Amp rating



**Model P82WC (White)
Premium Humidity Sensing Wall Control**

- Sensaire™ technology detects rising humidity to react to showers and clear mirrors quickly
- Variable setting from 20% to 80% relative humidity
- Can be used to comply with California Title 24 and CALGreen
- Precise sensitivity adjustment
- Continuous ventilation mode operates fan set minutes per hour to meet ASHRAE 62.2
- User-adjustable automatic shutoff timer
- LED indicator and manual operation mode
- Fits single-gang box
- 120 VAC, 60 Hz
- Requires neutral wire for operation



**Model P66WN (White)
Three-Funtion Control with Plastic Wall Plate**

- Three independent 120 V, 15 Amp rocker switches (20 Amp total)
- Fits single-gang box
- For use with all Broan or NuTone fans and heaters within Amp rating

Venmar Ventilation ULC; Drummondville, Québec www.broan.ca www.nutone.ca 877-896-1119

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by Date