BRSANNuTone



Add LED lighting to your bath fan with an easy-to-install grille upgrade kit.

Compatible with these Broan fan models:

If your grille looks like this

Compatible with these models*



Broan: 576, 670, 671, 674, 676, 678, 679, 680, 683, 684, 688, 689, 770, 771, 784, 679L, 683L, E050, E070, HD50, HD50L, HD80, HD80L

Existing fan housing sizes

 $7\frac{1}{2}$ " x $7\frac{1}{4}$ " and 8" x $8\frac{1}{4}$ "

In just 5 minutes you can add LED lighting to your bathroom.



Easily convert a non-lighted fan to a fan-light. Effective LED task lighting (equivalent 60W).



Stays cleaner longer. Fewer vent slots to clean, low-profile, streamlined design.



Fastest bath fan upgrade—5 minute, no cut, quick connect install.




Hides existing dry wall cuts—no cutting or professional installation required.

Compatible with these NuTone fan models:



Compatible with these models*



NuTone: 695, 763, 6950, 50NT, 684NT, 696N, 696N0, 763N, 80NT, HD50LNT, HD50LNT, HD80LNT, HD80NT

Existing fan housing sizes

7½" x 7¼" and 8" x 8¼"

*No other usage has been tested and authorized by Broan-NuTone LLC. For ceiling mount applications only. Visit Broan.com or NuTone.com for all compatible models.



Remove the old grille and unplug the motor.

Easy installation steps:



Choose grille springs matched to your fan model. Left: Factory-installed grille springs for fan models: 688, 671, 678 and 771. Right: Replace factory-

Right: Replace factoryinstalled grille springs with larger springs for fan models: 770, 676, 679 and 683.



Attach the grille to the fan housing with one grille spring. Plug the motor into the pass-through plug and the pass-through plug into the fan receptacle.



Attach the second grille spring to the fan and push the grille assembly against ceiling. You're done!



Watch the installation video youtu.be/Gzt20CAM25M

NuTone.com

Broan, 926 W. State Street, Hartford, WI 53027 800-558-1711